DAH Solar
www.dahsolarpv.com

TIER 1
BloombergNEF

GLOBAL PATENTS

DHM-66L9/FS(BB)

400~415W

[Full Screen] PV Module

No Dust and Dirt on the Surface Increases Power Generation

Quality Guarantee

12-year → Material & technology warranty

25-year → Linear power output warranty



DAH Solar Linear power output gurarantee
Standard Linear power output gurarantee

Comprehensive Products & System Certificates

IEC 61215 / IEC 61730 / CE / FIDE / INMETRO
ISO 45001 : 2018/International standards for occupational health & safety
ISO 14001 : 2015/Standards for environmental management system
ISO 9001 : 2015/Quality management system

No Water & Dust Accumulation, Increases Power Generation by 6-15%

Full-Screen PV Module has front frameless design, which decreases power loss and the O&M expenditures caused by the bottom dust shading.

Applied to All Mounting Scenarios

Full-Screen PV Module could apply to all the application scenarios, and the smaller angles of inclination, the higher power generation.

Preeminent Weather Resistance

Certified by Dust-Sand Test, Salt Spray Test, Ammonia Test, which allows the module to keep an excellent performance under the extreme weather conditions.

±0.1mm Production Accuracy Technology

Using excellent frame sealing technology makes the production accuracy achieve ±0.1mm to ensure the IP68 Waterproof and the mechanical load (front side: 5400Pa; back side: 2400Pa) . The ruggedness could compare with the architectural curtain wall.

DHM-66L9/FS(BB)

400~415W

GLOBAL PATENTS

Mechanical Specification

Cable	4.0mm², 350/250mm in length,
(Including connector)	length can be customized
No.of Cells	132 (6×22)
Glass	3.2mm High Transmission, Antireflection Coating
Junction box	IP68, 3 Bypass Diodes
Connector	MC4 Compatible
Weight	22kg
Cells Type	Mono 166×83mm
Dimension (L×W×T)	1924×1038×32mm
Packing	34pcs/pallet, 816pcs/40HQ

Operating Parameters

Maximum system voltage	1500V DC
Operating Temperature	-40 ~ +85°C
Maximum series fuse rating	20A
Snow load, frontside/Wind load, backside	5400Pa/2400Pa
Nominal operating cell temperature	45°C±2°C
Application level	Class A

Design



STC——Electrical Characteristics

Module Type	DHM-66L9/FS(BB)			
Maximum Power (Pmax/W)	400	405	410	415
Open-circuit Voltage (Voc/V)	44.8	45.0	45.2	45.4
Maximum Power Voltage (Vmp/V)	37.2	37.4	37.6	37.8
Short-circuit Current (Isc/A)	11.24	11.30	11.36	11.42
Maximum Power Current (Imp/A)	10.75	10.83	10.90	10.98
Module Efficiency (%)	20.03	20.28	20.53	20.78

Power Tolerance: 0~+5W, Temperature Coefficient of Isc: 0.05%/°C, Temperature Coefficient of Voc: -0.31%/°C, Temperature Coefficient of Pmax: -0.35%/°C

Standard Test Environment : Irradiance 1000W/m², Cell temperature 25°C, Spectrum AM1.5

NOCT——Electrical Characteristics

Maximum Power (Pmax/W)	298	301	305	309
Open-circuit Voltage (Voc/V)	42.0	42.2	42.4	42.6
Maximum Power Voltage (Vmp/V)	34.9	35.1	35.3	35.5
Short-circuit Current (Isc/A)	9.08	9.13	9.18	9.23
Maximum Power Current (Imp/A)	8.53	8.59	8.65	8.71

Standard Test Environment : Irradiance 800W/m², Ambient temperature 20°C, Spectrum AM1.5, Wind speed 1m/s

I-V Curve DHM-66L9/FS(BB)-415W

Current-Voltage Curve



Power-Voltage Curve



Current-Voltage Curve